


# O<sub>2</sub>

## Oxygen O2




Intelligent System to the new level of  
freedom and reliability


# ANPR - AUTOMATION

## Car Plate recognition

Oxygen will read the plate number and check with white list, to allow or disallow | Barrier gate will open or close as per the conditions. A snapshot will be recorded for future use and system can be accessible from anywhere in the world.



INTERNET DATA  
Internet data analysis | live reporting | news feeds | messengers | Social media





Oxygen O2 ANPR V10 - Web Site No: 803799 28th Oct, 2020 21:48:09

**LOG REPORT**

Export csv

Plate No	Count	Dir	Time	Country	Plate No	Vehicle Type	Owner	Address	Status	Camera	Group
544	1	D	21:33	UAE	L 9996	Van	Abu-Hussein		ALLOWED	CRK1	21:33
542	1	D	21:28	UAE	30450	Truck	NISSAN - Sunny		ALLOWED	CRK1	21:28
544	1	D	21:24	OO	OO	None	Not in the list	OO	NO ACCESS	CRK1	21:24
544	1	D	21:20	UAE	M3887	Truck	NISSAN		ALLOWED	CRK1	21:20
544	1	D	21:19	UAE	L 9996	Van	Abu-Hussein		ALLOWED	CRK1	21:19
542	1	D	21:18	UAE	L 9996	Truck	Abu-Hussein		ALLOWED	CRK1	21:18
542	1	D	21:14	OO	OO	Truck	Not in the list	OO	NO ACCESS	CRK1	21:14



+971 508031282



PO 299421 | Dubai | UAE




www.llct.net/o2

# ANPR - AUTOMATION



Oxygen v2



+971 508031282




PO 299421 | Dubai | UAE



[www.llct.net/o2](http://www.llct.net/o2)

# OXYGEN O<sub>2</sub>

## INTERNET OF THINGS



### TECHNICAL SPECIFICATION

Power supply	13V DC ±10%   110-230V 50Hz/60Hz AC UL
Power safe	Li Battery 4 AH[optional], Auto-shut down super capacitor protection
Working memory	1GB   2GB   4GB
Storage	64GB class 3
Extended storage	256GB SSD [Optional]
Cloud	Amazon AWS Dedicated server
Out put control	<b>8x</b> 10A 220V   5A 30V DC, Dry contact out
Working Temperature	- 10°C up to 60°C
Connectivity	IEEE 802.11.b/g/n/ac wireless LAN 2.4GHz and 5GHz Bluetooth 4.2/BLE, faster Ethernet
Processor power	Quad-core processor, Cortex-A53 (ARMv8) 64-bit SoC @ 1.4GHz
Ports	<b>1x</b> HDMI 1.4, <b>4x</b> USB 2.0 ports
Input / Output	<b>8x</b> Dry contact out put Digital out <b>8x</b> Digital logical input - Isolated industrial <b>128x</b> Digital input expansion over i2C [optional]
Dimension [HxWxD]	46mm x 482mm x 90mm
External connections Protocols	I2C, 1Wire, TCPIP, Wifi, MODBUS[optional], Zigbee[optional] Zwave[optional], MQTT, GPIO, HDMI-Audio video, 433Mhz RF
Integration	amazon echo, Google Home, Apple Home kit, Grafana, HTML5, NODE JS, Python, MQTT, Node Red, Artificial Intelligence

### Monitoring Application

Exit Door monitoring  
Facility monitoring  
Temperature monitoring  
Sound level monitoring  
Environment monitoring  
Light intensity monitoring

CO2 monitoring  
Water detect  
Moisture level monitoring  
Altitude, Vibration  
GPS location sensing  
Atmosphere pressure sensing

### Control Application

Office Automation  
Home Automation  
Out door lighting  
Robotics, Automation  
Programmable logical Control  
Lighting/Motor control

IF THEN DO THIS  
Input vs Output control  
Timer control  
UAE Adan system  
Centralized audio player  
Timed Audio player

### MULTIPLE INTEGRATIONS



### CONTACT

LLCT, PO Box 299421  
AL Nisf Building, Airport Road  
Dubai, UAE [www.llct.net/oxygen](http://www.llct.net/oxygen)  
(+971) 508031282 | [oxygen@llct.net](mailto:oxygen@llct.net)

LLCT, KINFRA Park [Branch]  
Thiruvanthapuram, Kerala, INDIA  
[oxygen\\_tvm@llct.net](mailto:oxygen_tvm@llct.net)

