

CCTV PRODUCTS & IP SOLUTIONS

PRODUCT LINE-UP



We Leaders Line Trading L.L.C. is a multi-disciplined systems integrator in UAE having office in Dubai International City We help our clients to plan, design and manage their Security system infrastructure through a wide product range includes

- CCTV (Dubai police Approved CCTV installer)
- Time, Attendance and Access control System
- Structured cabling, Data Networking, LAN, MAN, Wireless LAN
- BGM – Centrally Managed Background Music system
- Data Centers, Storage and server implementation
- Security System designing (Both Hardware and Software)
- Video Wall solutions



NVR

Super Series	Desktop Series	
<p>NVR6000/6000D/6000DR</p>  <p>128CH 3U Super NVR</p>  <ul style="list-style-type: none"> Up to 128ch IP camera inputs 1ch audio & 1ch Mic in, 1ch audio out 128ch@D1, 64ch@720p, 32ch@1080p Compatible with D1, 720p, 1080p, 3Mp, 5Mp etc. 6 HDMI sync output/1 VGA & 5 HDMI sync output 16/8ch alarm in/out, Hot-Swap HDD, RAID 0/1/5 16ch sync realtime playback 16 SATA, 1 eSATA, 4 USB, 4 RJ45(1000M) <p>* -D: LCD screen; -DR: LCD screen, Redundant power supply module; Default: 2 HDMI</p>	<p>NVR3804/3808/3816</p>  <p>4/8/16CH 2U NVR</p>  <ul style="list-style-type: none"> 4/8/16ch IP camera inputs 1/1ch Mic in/out Max 120fps@1080p, 240fps@720p, 480fps@D1 HDMI, VGA output up to 1080p, 1 TV 4/8/16ch alarm in & 6ch relay out, RS485 8 SATA, 1 eSATA, 4 USB, RJ45(1000M) 	<p>NVR3204/3208/3216</p>  <p>4/8/16CH 1U NVR</p>  <ul style="list-style-type: none"> 4/8/16ch IP camera inputs 1/1ch Mic in/out Max 120fps@1080p, 240fps@720p, 480fps@D1 HDMI, VGA output up to 1080p, 1 TV 4/8/16ch alarm in & 3ch relay out, RS485 2 SATA, 2 USB, RJ45(1000M)
<p>IPC Support list:</p> 		

Professional DVR

<p>DVR0404/0804/1604HF-SH</p>   <p>4/8/16CH Full D1 High-performance 2U DVR</p> <ul style="list-style-type: none"> 4/8/16ch video & audio H.264 & Dual-stream encoding Full channel@D1(4CIF) realtime recording Dual-HDMI,VGA output up to 1080p, 1 TV, 1 Spot, 16 Loop Hotswap HDD, pluggable front panel, RAID0/1/5/10 8 SATA, 1 eSATA, 4 USB, 2 RJ4 	<p>DVR0404/0804/1604/2404/3204HF-S</p>   <p>4/8/16/24/32CH Full D1 2U DVR</p> <ul style="list-style-type: none"> 4/8/16/24/32ch video & 4/8/16/16/16ch audio H.264 & Dual-stream encoding Full channel@D1(4CIF) realtime recording HDMI,VGA output up to 1080p, 1 TV, 1 spot, 16 loop(DVR0404/0804/1604 HF-S) 8 SATA, 1 eSATA, 3 USB 4 USB(DVR3204HF-S) 	<p>DVR0404/0804/1604HF-L</p>   <p>4/8/16CH Full D1 1.5U DVR</p> <ul style="list-style-type: none"> 4/8/16ch video & 4ch audio H.264 & Dual-stream encoding Full channel@D1(4CIF) realtime recording HDMI, VGA output up to 1080p, 1 TV, 1 Spot, 16 Loop 4 SATA, 1 eSATA, 2 USB
--	--	---

Network Camera

3 Megapixel Series

IPC-HFW3300



3Megapixel Full HD Network IR Camera

- 1/2.8" 3Mp Exmor CMOS
- H.264/MJPEG & dual-stream encoding
- Max 20fps@3M(2048x1536), 25/30fps@1080p
- Lens: 8~16mm/F1.6, IR LEDs: 30m
- D&N(ICR), Auto Iris, Micro SD card
- IP66, DC12V(AC24 optional), PoE

3 Megapixel Series

IPC-HDBW3300



3Megapixel Full HD Vandal-proof Network IR Dome Camera

- 1/2.8" 3Mp Exmor CMOS
- H.264/MJPEG & dual-stream encoding
- Max 20fps@3M(2048x1536), 25/30fps@1080p
- Lens: 3.3~12mm/F1.4, IR LEDs:20m
- D&N(ICR), Auto Iris, Micro SD card
- IK10, IP66, AC24V/DC12V, PoE

IPC-HDBW3202



2Megapixel Full HD Vandal-proof Network Dome Camera

- 1/3" 2Mp Exmor CMOS
- H.264/MJPEG & dual-stream encoding
- Max 25/30fps@1080p
- Lens: 3.3~12mm/F1.4 (3200)
- Motorized Lens: 3~9mm/F1.2 (3202)
- D&N(ICR), Auto Iris, Micro SD card
- IK10, IP66, AC24V/DC12V, PoE

IPC-HF3200



2Megapixel Full HD Network Camera

- 1/3" 2Mp Exmor CMOS
- H.264/MJPEG & dual-stream encoding
- Max 25/30fps@1080p
- D&N(ICR), Auto Iris, SD card
- Wi-Fi(optional), AC24V/DC12V, PoE

IPC-HFW3200C



2Megapixel Full HD Network IR-Bullet Camera

- 1/3" 2Mp Exmor CMOS
- H.264/MJPEG & dual-stream encoding
- Max 25/30fps@1080p
- Lens: 3.3~12mm/F1.4, IR LEDs: 20m
- D&N(ICR), Auto Iris, Micro SD card
- IP66, DC12V(AC24 optional), PoE

IPC-HDB3200C



2Megapixel Full HD Vandal-proof Network Mini Dome Camera

- 1/3" 2Mp Exmor CMOS
- H.264/MJPEG & dual-stream encoding
- Max 25/30fps@1080p
- Lens: 3.6(2.8mm, 6mm, 8mm optional)
- Micro SD card
- IK10, IP66, DC12V, PoE

Analog Camera

WDR Effio-E Series

CA-DB581B



700TVL Day/Night WDR Vandal-proof Zoom Dome Camera

- 1/3" Super HAD CCD II
- 700TVL(Color), 750TVL(B/W)
- 0.005Lux/F1.4(Color), 0.0005Lux/F1.4(B/W)
- Lens: 4~9mm(2.8~12mm optional)
- D&N(ICR), WDR, Auto iris, OSD
- IK10, IP66, DC12V/AC24V

Standard Effio-E Series

CA-F781E



700TVL Day/Night Low Light Camera

- 1/3" EXview HAD CCD II & Effio-S
- 700TVL(Color), 750TVL(B/W)
- Color: 0.001Lux/F1.2, 0.0001Lux/F1.2(slow shutterx512)
- B/W: 0.0001Lux/F1.2, 0.00001Lux/F1.2(slow shutterx512)
- D&N(ICR), Auto iris, OSD
- AC24V/DC12V

CA-F781D



700TVL Day/Night Low Light Camera

- 1/3" EXview HAD CCD II & Effio-S
- 700TVL(Color), 750TVL(B/W)
- Color: 0.001Lux/F1.2, 0.0001Lux/F1.2(slow shutterx512)
- B/W: 0.0001Lux/F1.2, 0.00001Lux/F1.2(slow shutterx512)
- Lens: 2.7~9mm
- D&N(ICR), Auto iris, OSD
- AC24V/DC12V

CA-FW480E



700TVL Waterproof IR Camera

- 1/3" EXview HAD CCD II
- 700TVL(Color), 750TVL(B/W)
- 0.02Lux/F1.2, 0Lux (IR On)
- Motorized Lens: 4~9mm(8~20mm optional)
- IR LEDs: 50m(100m optional), Smart IR, IP66, DC12V
- Default: with Bracket

CA-D480



700TVL Mini Dome Camera

- 1/3" EXview HAD CCD II
- 700TVL(Color), 750TVL(B/W)
- 0.05Lux/F1.2(Color)
- Lens: 3.6mm(2.8mm, 6mm, 8mm optional)
- OSD, DC12V

CA-D480B



700TVL Dome Camera

- 1/3" EXview HAD CCD II
- 700TVL(Color), 750TVL(B/W)
- 0.05Lux/F1.2(Color)
- Lens: 4.0~9.0mm(2.8~12mm optional)
- Auto iris, OSD
- AC24V/DC12V

CA-FW171D



600TVL Water-proof IR Camera

- 1/3" HDIS
- 600TVL(Color)
- 0.1Lux/F1.2(Color), 0Lux(IR on)
- Lens: 6mm(3.6mm, 8mm optional)
- D&N(ICR)
- IR LEDs: 50m
- IP66, DC12V

CA-D170C



600TVL Mini Dome Camera

- 1/3" HDIS
- 600TVL(Color)
- 0.1Lux/F1.2(Color)
- Lens: 3.6mm(2.8mm, 6mm, 8mm optional)
- Advanced tri-axis structure adopted & support 355° pan
- DC12V

CA-DW171E



600TVL Water-proof IR Mini Dome Camera

- 1/3" HDIS
- 600TVL(Color)
- 0.1Lux/F1.2(Color)
- Lens: 3.6mm(6mm optional)
- D&N(ICR)
- IR LEDs: 20m
- IP66, DC12V

*Design and specifications are subject to change without notice.



ليدزس لاين للتجارة ش.ذ.م.م مكتب ١١، ٧. ج، مدينة دولية، دبي، الإمارات العربية المتحدة

Address : Leaders Line Trading LLC, PO Box 299421, S11, J07 - International city, Dubai, UAE

T : +971 4422 4008 .. F : 044 23 1151 .. www.llct.net | sales@llct.net

